# FUJITSU

# DATASHEET
# FUJITSU DISPLAY SL22W-1 LED DISPLAY

ADVANCED DISPLAY: 55.9 CM (22-INCH) WIDESCREEN
BEST PERFORMANCE AND ENERGY SAVING SOLUTIONS FOR HOME AND OFFICE
APPLICATIONS

The SL22W-1 LED comes in a 16:10 format with a eye-catching piano black ultra slim design. With the 3 ms resonse time and the ultra high 5,000,000:1 contrast ratio (ACR) it is the display for perfect home entertainment. There is no compromise in picture quality and energy efficiency. It is intuitive to handle thanks to sensor keys and support languages.

Widescreen display with LED backlit panel in optimum 16:10 format

3 ms fast response time - perfect for gaming, internet and office

1680 x 1050 HD resolution for excellent entertainment and work experience

Touch sensor keys for smart adjustments

Due to integrated speakers no further accessories needed

Green IT | ENERGY STAR | EPEAT SILVER | Compatible with Windows 7

| LED BACKLIGHT | ECO MODE LED | ACR CONTRAST | RESPONSE TIME | TOUCH SENSOR | HDCP | LIGHT WEIGHT | SPEAKER | AC INPUT |

# TECHNICAL DETAILS

## SPECIAL FEATURES

| | |
|---|---|
| | LED backlit panel, 6 + 1 touch sensor keys, ECO Status LED: 3 colors for 3 modes, keep aspect ratio option |

## STAND DETAILS

| | |
|---|---|
| Stand | removable |
| Picture height over desk (min) | 96 mm |
| Tilt angle | -5° / +15° |

## PICTURE PERFORMANCE

| | |
|---|---|
| Contrast  - typical | 1000:1 |
| Contrast  - advanced | 5,000,000:1 |
| Response time gray to gray typical | 3 ms |
| Viewing angle (h/v) | 170° / 170° |
| Color performance | 16.7 million colors (Hi-FRC) |
| Brightness - typical | 250 cd/m² |

## SIZE AND RESOLUTION

| | |
|---|---|
| Aspect ratio | 16:10 |
| Diagonal Size | 55.9 cm (22-inch) |
| Resolution (native) | 1680 x 1050 pixel (recommended) |
| Resolution (interpolated) | 1280 x 1024 pixel, 1024 x 768 pixel, 800 x 600 pixel |
| Picture size | 474  mm x 296 mm |
| Pixel Pitch | 0.282 mm |

## FREQUENCIES

| | |
|---|---|
| Horizontal analog | 30 kHz to 82 kHz |
| Horizontal digital | 15 kHz to 82 kHz |
| Vertical | 55 - 76 Hz |
| Frequencies - bandwidth | 205 MHz |

## CONNECTIVITY

| | |
|---|---|
| Video Input | 1 x DVI (HDCP)<br>1 x D-SUB |
| Audio sound output | 2 x 1 W |
| Audio signal input | 3.5 mm stereo phone jack |

## OSD LANGUAGES AND SETTING OPTIONS

| | |
|---|---|
| Languages | Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish |
| Brightness / Contrast | Brightness, Contrast, Black level, Auto level |
| Color | 6500K, 7500K, 9300K, Native, sRGB, Custom Color |
| Image adjust | H-Position, V-Position, Sharpness, Clock, Phase |
| Audio | Mute, Volume |
| Information | Resolution/mode, Signal input |
| Mode | General, Movie, Picture, Game |

## POWER CONSUMPTION (TYPICAL, W/O SOUND)

| | |
|---|---|
| Soft switch off | 0.32 W |
| Power save mode | 0.33 W |
| Operating with EPA settings | 23.1 W |
| Operating maximum brightness | 25.7 W |

## ELECTRICAL VALUES

| | |
|---|---|
| Rated voltage range | 100 - 240 V |
| Rated frequency range | 50 - 60 Hz |
| Protection class | 1 |

## COMPLIANCE

| | |
|---|---|
| **Europe** | CE |
| **USA/Canada** | FCC Class B, cUL |
| **Russia** | GOST |
| **Saudi Arabia** | SASO |
| **Global** | ENERGY STAR® 5.0, ISO9241-307 (Pixel fault class I), IT-Eco-Declaration, RoHS, WEEE |
| **Compliance link** | https://sp.ts.fujitsu.com/sites/certificates/default.aspx |

## QUALITY AND RELIABILITY

| | |
|---|---|
| **MTBF (demonstrated)** | 50000 h |

## DIMENSIONS / WEIGHT

| | |
|---|---|
| **Dimension without stand  (W x D x H)** | 512 x 44 x 352 mm |
| **Dimension with stand  (W x D x H)** | 512 x 189 x 413 mm |
| **Weight (unpacked)** | 3.3 kg |
| **Operating ambient temperature** | 5 - 35°C |

## MISCELLANEOUS

| | |
|---|---|
| | VESA DDC/ CI, Kensington lock |

## PACKAGE CONTENT

| | |
|---|---|
| | Data cable 1.8m, D-SUB (15-pin), Audio cable 1.8m, Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8m, User manual, Warranty booklet, Quickstart flyer |
| | Data cables and audio cable detachable on display |

## ORDER INFORMATION

| | |
|---|---|
| **Order Code** | S26361-K1364-V160 |
| **EAN-No.** | 4049699259371 |

## WARRANTY

| | |
|---|---|
| **Service level** | (depending on country) |
| **Service Weblink** | http://ts.fujitsu.com/Supportservice |

## FUJITSU PLATFORM SOLUTIONS

In addition to Fujitsu Display SL22W-1 LED, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

### Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

### Computing Products

www.fujitsu.com/global/services/computing/

### Software

www.fujitsu.com/software/

## MORE INFORMATION

Learn more about Fujitsu Display SL22W-1 LED, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. http://ts.fujitsu.com/displays

## FUJITSU GREEN POLICY INNOVATION

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT.
Please find further information at http://www.fujitsu.com/global/about/environment/



## COPYRIGHTS

## DISCLAIMER

## CONTACT

FUJITSU Technology Solutions
Website: http://ts.fujitsu.com
2010-06-18 CE-EN