

Fujitsu recommends Windows® 7.

# Data Sheet

## Fujitsu ESPRIMO C700 Desktop PC

Your Ultra Small Form Factor PC

The Fujitsu ESPRIMO C700 has an ultra-small form factor with a volume of less than 8-liters, making it ideal for your space-constrained office. A 90%-efficient power supply and Intel® Standard Manageability will lower your energy and administrative costs. A professional Intel® Core™ processor ensures great performance. Plus, EraseDisk ensures secure system retirement.



### Ultra small form factor PC

Top quality PC for office environments with little space; can be positioned both horizontally and vertically

- Only 7.4 liters volume, integrated & high efficient power supply, legacy interfaces and powered serial ports

### Energy efficiency coupled with intelligent performance

Low power consumption combined with top performance

- 2nd generation Intel® Core™ processors with Turbo Boost 2.0 and Hyper-Threading technology, energy efficient power supply up to 90% and ENERGY STAR® certification

### Compact but expandable

Compact Fujitsu ESPRIMO PC with discrete graphics card supporting multi-monitoring

- Up to a 500 GB disk and PCIe x16 slot



### Family concept

Reduced test and evaluation costs for the existing PC infrastructure

- Uniform technology platform and bit image for the Fujitsu 700 series

### Green technology

Fujitsu's contribution to environmental protection for the continued existence of our planet

- Halogen-free printed circuit of mainboard and power supply, sophisticated product concept for the entire lifecycle



# Components

<b>Processor</b>	Intel® Core™ i5-2400 processor (4 Cores / 4 Threads, 3.10 GHz, 6 MB, Intel® HD Graphics 2000) Intel® Core™ i3-2120 processor (2 Cores / 4 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 2000) Intel® Pentium® processor G850 (2 Cores / 2 Threads, 2.90 GHz, 3 MB, Intel® HD Graphics)
<b>Operating systems</b>	
<b>Operating system</b>	Windows® 7 Home Basic (EM) 32-bit Windows® 7 Home Premium 64-bit Windows® 7 Professional 32-bit Windows® 7 Professional 64-bit
<b>Operating system compatible</b>	openSUSE Linux Windows Vista® Windows® XP
<b>Operating system notes</b>	Limited Windows® XP support. Microsoft discontinued Windows® XP certification on system level, basic drivers via <a href="http://support.ts.fujitsu.com">http://support.ts.fujitsu.com</a>
<b>Memory modules</b>	2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1333 MHz, PC3-10600, DIMM 4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1333 MHz, PC3-10600, DIMM
<b>Hard disk drives (internal)</b>	SSD SATA III, 256 GB, 2.5-inch SSD SATA III, 128 GB, 2.5-inch SSD SATA II, 128 GB, 2.5-inch, FDE mSATA, 16 GB, Flash drive mSATA, 8 GB, Flash drive mSATA, 4 GB, Flash drive mSATA, 2 GB, Flash drive mSATA, 1 GB, Flash drive HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch HDD SATA III, 7200 rpm, 500 GB, 3.5-inch, business critical HDD SATA III, 7200 rpm, 500 GB, 3.5-inch HDD SATA III, 7200 rpm, 250 GB, 3.5-inch HDD SATA II, 7200 rpm, 320 GB, 2.5-inch HDD SATA II, 7200 rpm, 160 GB, 2.5-inch
<b>Hard disk notes</b>	Up to 18 GB of HDD space is reserved for system recovery
<b>Graphics add on cards (optional)</b>	NVIDIA® Quadro® NVS 300 LP, 512 MB LFH59/ 2x DVI-I adapter cable LFH59/ 2x DP adapter cable DP to DVI-D (single link) Adapter Cable
<b>Drives (optional)</b>	BD Triple Writer SATA slim (tray) DVD SuperMulti SATA slim DVD Super Multi Slot-in slim
<b>Interface add on cards/components (optional)</b>	WLAN III, 802.11g/Draft-n (Windows only) USB 3.0 PCIe x1 Parallel Interface Gigabit Ethernet PCIe x1, DS eSATA Interface Dual serial card PCIe x1, powered Dual serial card PCIe x1
<b>Base unit</b>	ESPRIMO C700

**Mainboard**

Mainboard type	D3064
Formfactor	proprietary
Chipset	Intel® Q65
Processor socket	LGA 1155
Processor quantity maximum	1
Memory slots	4 DIMM (DDR3)
Supported capacity RAM (max.)	32 GB
Memory frequency	1333 MHz
Memory notes	Dual channel support. For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules). > 16 GB support with future memory modules
LAN	10/100/1000 MBit/s Intel® 82579 V
BIOS version	AMI Aptio 4.6
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio codec	Conexant CX20642
Audio features	Internal speaker supports audio playback, High Definition audio

**I/O controller on board**

Serial ATA total	3
Controller functions	Serial ATA II (3 Gbit) Serial ATA III (6 Gbit) NCQ AHCI

**Interfaces**

Audio: line-in	1
Audio: line-out	1
Front audio: microphone	1
Front audio: headphone	1
USB 2.0 total	12
USB 3.0 total	optional
USB front	4
USB rear	6
USB internal	2
VGA	1 (via DVI to VGA adapter, part of shipment)
DisplayPort	1
DVI	1 (DVI-I)
Serial (RS-232)	2 (powered, 9pin, 16 byte FIFO, 16550 compatible)
Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1
Parallel	1 (optional) (25pin with EPP and ECP)
eSATA	1 (optional)
Interface Module notes	Anytime USB charge functionality

**Input device / components**

Input devices (optional)	Optical USB tilt wheel mouse Optical USB/PS2 tilt wheel mouse KBPC PX ECO
--------------------------	---

**Drive bays**

Drive bays total	2
3.5-inch internal bays	1
5.25-inch external bays	1
Drive bay notes	slim optical disc drive

**Slots**

PCI-Express 2.0 x16	1 x (220 mm / 8.66 inch) Low profile
---------------------	--------------------------------------

**Graphics on board**

<b>Graphics brand name</b>	Intel® HD Graphics or HD Graphics 2000 (depending on CPU)
<b>Shared video memory</b>	up to 1759 MB
<b>TFT resolution (VGA)</b>	1024 x 768 pixel 1280 x 1024 pixel 1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1600 x 1200 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel
<b>TFT resolution (DVI)</b>	1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel
<b>TFT resolution (DisplayPort)</b>	1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel 2560 x 1440 pixel 2560 x 1600 pixel
<b>Graphics features</b>	Dual display support DirectX 10.1 HDCP support OpenGL® 2.1 For multi monitoring mode, graphics card and integrated graphics run in parallel (Microsoft® Windows 7® only)
<b>Graphics notes</b>	Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz

**Electrical values**

<b>Power efficiency note</b>	power supply efficiency (at 230V; 20% / 50% / 100% load) : 87% / 90% / 87%
<b>Rated voltage range</b>	100 V - 240 V
<b>Rated frequency range</b>	50 Hz - 60 Hz
<b>Operating voltage range</b>	90 V - 264 V
<b>Operating line frequency range</b>	47 Hz - 63 Hz
<b>Max. output of single power supply</b>	225 W
<b>Power factor correction/active power</b>	active
<b>Monitor outlet</b>	No

**Power consumption**

<b>Power consumption note</b>	See white paper Energy Consumption
-------------------------------	------------------------------------

**Heat dissipation**

<b>Heat dissipation notes</b>	See white paper Energy Consumption
-------------------------------	------------------------------------

**Noise for standard configuration (HDD, ODD)**

<b>Noise emission</b>	According to ISO9296
<b>Related Processors for noise</b>	Core i3-2100 ; Core i5-2400
<b>Noise Operation mode 1: ODD load (Blue angel requirement)</b>	4.6 B / 32 dB(A) ; 4.8 B / 32 dB(A)

**Noise for standard configuration (HDD, ODD)**

Noise Operation mode 2: HDD load (Blue angel requirement)	3.6 B / 22 dB(A) ; 3.6 B / 22 dB(A)
Noise Operation mode 3: CPU 90% load (Blue angel requirement)	3.6 B / 22 dB(A) ; 3.9 B / 25 dB(A)
Noise Operation mode 4: High load	3.7 B / 22 dB(A) ; 4.0 B / 25 dB(A)
Noise Operation mode 5: Office applications 2.0	3.6 B / 22 dB(A) ; 3.7 B / 22 dB(A)
Idle mode (Blue Angel requirement)	3.6 B / 22 dB(A)
Noise notes / description	A weighted sound power level L <sub>wad</sub> (in B) / workplace related A-weighted sound pressure level L <sub>pAm</sub> (in dB(A)), Bystander position

**Dimensions / Weight / Environmental**

Dimensions (W x D x H)	265 x 315 x 88 mm 10.44 x 12.4 x 3.47 inch
Operating position	Vertical / horizontal (no feet needed)
Weight	9 kg
Weight (lbs)	20.2 lbs
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35°C (50 - 95°F)

**Compliance**

Product	ESPRIMO C700
Model	USD
Germany	TÜV GS
Europe	CE Nordic Swan
USA/Canada	FCC Class B CSA
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® EPEAT® Gold (dedicated regions)
Compliance link	<a href="https://sp.ts.fujitsu.com/sites/certificates/">https://sp.ts.fujitsu.com/sites/certificates/</a>

**Additional Software**

Additional software (preinstalled)	Nero Essentials S (burning software) Fujitsu Recovery (Hard Disk Based Recovery) Norton Internet Security (incl. Firewall) 60 days version Microsoft® Office Starter: reduced-functionality Word and Excel® only, with advertising. No PowerPoint® or Outlook®. Buy Office 2010 to use the full-featured software.
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) Nero 9 Essentials XL

**Miscellaneous**

	Keyboard on (Special Fujitsu keyboard required) Thermal management Extended lifetime
--	--

**Compatibility (references)**

	DMI 2.0 PC 2001 WMI 1.5 USB 2.0 SMBIOS
--	--

**Manageability**

<b>Manageability technology</b>	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) Intel® Standard Manageability WoL (Wake on LAN)
<b>Manageability software</b>	DeskView Client DeskView Instant BIOS Management DeskView Integration for Symantec Management Platform
<b>DeskView components</b>	Inventory Management BIOS Management Driver Management Security Management Alarm Management
<b>Manageability link</b>	<a href="http://ts.fujitsu.com/manageability">http://ts.fujitsu.com/manageability</a>

**Security**

<b>System protection</b>	Kensington Lock support Eye for padlock Optional: Integrated cabinet lock
<b>Audit proof protection</b>	EraseDisk (optional) Boot sector virus protection Write protect option for the Flash EPROM Embedded security (TPM 1.2) Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces
<b>Access protection</b>	User and supervisor BIOS password Hard disk password Optional: Access protection via external SmartCard reader Optional: Access protection via internal SmartCard reader

**Serviceability**

EasyFix  
EasyChange for HDD

**Packaging information**

<b>Packaging dimension (mm)</b>	467 x 265 x 540 mm
<b>Packaging dimension (inch)</b>	18.39 x 10.43 x 21.26 inch
<b>Max. quantity / pallet</b>	28
<b>Material - Weight (g) Carton</b>	940 g
<b>Material - Weight (lbs) Carton</b>	2.07 lbs
<b>Material - Weight (g) EPS / PS</b>	190 g
<b>Material - Weight (lbs) EPS / PS</b>	0.42 lbs
<b>Material - Weight (g) PE</b>	60 g
<b>Material - Weight (lbs) PE</b>	0.13 lbs
<b>Packaging notes</b>	printed user documentation is bleached in chlorine free process

**Warranty**

<b>Standard Warranty</b>	1 year
<b>Service level</b>	Bring-In / On-Site Service (depending on country)
<b>Maintenance and Support Services - the perfect extension</b>	
<b>Recommended Service</b>	5x9, Response Time: Next Business Day
<b>Spare Parts availability</b>	5 years
<b>Service Weblink</b>	<a href="http://www.fujitsu.com/fts/services/support/index.html">http://www.fujitsu.com/fts/services/support/index.html</a>

## Recommended Accessories

### Wireless Keyboard Set LX900



The Wireless Keyboard LX900 is a top of the line desktop solution for lifestyle orientated customers, who want only the best for their desk. This superb keyboard set with offers ambitious users more functions, security and better features than a conventional interface device. It even includes 2.4 GHz technology and 128 AES encryption for security.

S26381-K564-L4\*\* (\*\*: Country specific variation)

### Keyboard KBPC PX ECO



Fujitsu's KBPC PX ECO keyboard is the perfect contribution to Green IT. The keyboard is made out of 45% renewable raw material and comes with a PVC free USB cable. In addition, the KBPC PX ECO offers first class comfort and ergonomics. It attracts attention with its impressive modern design and useful extras.

S26381-K341-L1\*\* (\*\*: country specific variation)

### SOUNDSYSTEM DS E2000 Air



The new more powerful SOUNDSYSTEM DS E2000 Air gives you impressive, well-balanced sound throughout the frequency band. It is an unbeatable USB speaker set with a surprisingly small form factor. The robust satellite speakers are decorated with a deluxe piano finish and the base is adorned with warm ambient lighting.

Order Code:  
S26391-F7128-L600

### WebCam 130 HD2



With the most advanced HD (High Definition / 720p) recording feature and widescreen video format (16:9 and 16:10), WebCam 130 HD2 can capture up to 30 frame rate per second, close up to HD/720p quality video. Even more: 1-Click-Upload makes the video uploading to YouTube in a snap! With smart clip for notebook & LCD display it is easy to install on any device you want.

Order Code:  
S26391-F7136-L5

### HS E2000 Communicator Headset



The Fujitsu HS E2000 Communicator headset allows you to use your personal computer for Voice over IP (VoIP) in stereo audio quality. This premium headset is designed to provide superb audio quality and comfort for the telephony, internet chat, speech recognition, video conferencing and multimedia applications.

Order Code:  
S26391-F7139-L5

### CELVIN® Drive D100



The CELVIN® Drive D100 is a highly reliable external storage device with a standard USB-interface for easy Plug & Play use with a notebook or PC. It is also easy to set up additional home network capacity by connecting it with dedicated routers or NAS devices.

Order Code:  
S26341-F103-L116

## More information

### Fujitsu OPTIMIZATION Services

In addition to Fujitsu ESPRIMO C700, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

### Computing Products

[www.fujitsu.com/global/services/computing/](http://www.fujitsu.com/global/services/computing/)

### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

### More information

Learn more about Fujitsu ESPRIMO C700, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
[www.fujitsu.com/fts/ESPRIMO](http://www.fujitsu.com/fts/ESPRIMO)

### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at <http://www.fujitsu.com/global/about/environment/>



### Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.  
For further information see [www.fujitsu.com/terms](http://www.fujitsu.com/terms)  
Copyright © Fujitsu Technology Solutions

### Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

### Contact

FUJITSU Technology Solutions  
Website: [www.fujitsu.com/fts](http://www.fujitsu.com/fts)  
2012-09-27 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.  
For further information see [www.fujitsu.com/terms](http://www.fujitsu.com/terms)  
Copyright © Fujitsu Technology Solutions